


1.25Gb/s 15Km SFP



RTXM191-404

TX_fault /LOS	1	Icc	mA	-	-	300
				mV	150	1100
				mV	300	600
				VOH	V	2.0
				VOL	V	0
				VOH	V	2.0
				VOL	V	0
				Po	dBm	-9
				λc	nm	1270
				EX	dB	9
TX_disable	(TTL)	VOH	V	2.0	-	Vcc
				0	-	0.8
				2.0	-	Vcc
				0	-	0.8
				Po	dBm	-3
				λc	nm	1355
				EX	dB	9
				Δλ	nm	4
				TJ	UI	0.284
				RIN	dB/Hz	-120
(RMS)	2	RIN	dB/Hz	GE		
				Trise/Tfall	ps	260
				-	dB	1
				Poff	dBm	-45
				λc	nm	1250
				S	dBm	-20
				Pin	dBm	-3
/	3	Trise/Tfall	ps			
	4	λc	nm	1250		1620

		dB	0.5		5
Note1. Note2. 1.25Gbps 7 Note3. RIN 12dB Note4. PRBS 2 ⁷ -1 1.25Gb/s EX=10dB BER<10 ⁻¹²					

RTXM191-404	SFP	1.25G	1310nm FP	-9~ -3dBm	PIN	< -20dBm	-40~85°C	15km	DDM, RoHS