

10Gbps XFP Optical Transceiver RTX226-440

Specifications

(T

10Gbps XFP Optical Transceiver RTX226-440

Ordering Information

Absolute Maximum Ratings

Parameter	Symbol	Unit	Min	Max
Supply Voltage 1	V _{CC3}	V	-0.5	4.0
Supply Voltage 2	V _{CC5}	V	-0.5	6.0
Storage Temperature	T _s	°C	-40	85

10Gbps XFP Optical Transceiver RTX226-440

Low Speed Electrical Interface

Parameter	Symbol	Unit	Min	Max	Note
XFP Tx_Dis,P_Down/RST	V _{IH}	V	2.0	V _{cc3} +0.3	
	V _{IL}	V	-0.3	0.8	
XFP Interrupt,Mod_NR,Rx_Los	V _{OH}	V	V _{dd3} -0.5	V _{dd3} +0.3	1
	V _{OL}	V	0.0	0.4	
XFP SCL and SD Input	V _{IH}	V	V _{dd3} *0.7	V _{dd3} +0.5	1
	V _{IL}	V	-0.3	V _{dd3} *0.3	
XFP SCL and SD Output	V _{OH}	V	V _{dd3} -0.5		

10Gbps XFP Optical Transceiver RTX226-440

10Gbps XFP Optical Transceiver RTX226-440


Digital Diagnostic Functions

As defined by the XFP MSA, digital diagnostic functions are provided via a 2-wire serial interface, which allows real-time access to the following operating parameters:

- Transceiver Temperature
- Tx Bias Current
- Tx Optical Power
- RX Received Optical Power
- Transceiver +3.3V Supply Voltage
- Laser Temperature

10Gbps XFP Optical Transceiver RTX226-440

Package Outline



Regulatory Compliance

Feature	Test Method	Performance
Laser Eye Safety	FD 21 CFR 1040.10 and 1040.11 IEC 60825-1: 1994+ 11: 1996+ 2: 2001 IEC 60825-2: 2004 + 1: 2006 EN 60825-1:1994+ 1:2002+ 2:2001 EN 60825-2: 2004	Compliant with Class 1 laser product
Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7 Human Body Model	Class 1 (1.5kV)
Electrostatic Discharge (ESD) Immunity	IEC 61000-4-2: 2001	Class 2 (4.0kV)
Electromagnetic Interference (EMI)	FCC Part 15 Subpart J Class B CISPR22:1997+ 1:2000+ 2:2002, Class B EN55022:1998+ 1:2000+ 2:2003, Class B	Compliant with standards